

GENERAL SPECIFICATIONS	
Frequency	PMR446MHz
Channel Capacity	16 Channels
Channel Spacing	12.5KHz
Operating Voltage	7.4VDC ±20%
Frequency Stability	±2.5ppm
Operating Temperature	-20°C~ +55°C
Dimensions	260x60x35mm(with Battery Pack)
Weight	208g (with Battery Pack)

TRANSMITTER SPECIFICATIONS		
Output Power	0.5W	
Adjacent Channel Power	65dB	
Hum & Noise	40dB	
Spurious Emission	-36dB	
Audio Distortion	5%	

RECEIVER SPECIFICATIONS		
Sensitivity (@12dB SINAD)	0.35uV	
Adjacent Channel Selectivity	60dB	
Spurious Rejection	70dB	
Intermodulation	60dB	
Hum & Noise	36dB	
Audio Distortion	5%	
Audio Output Power	1000mW/16Ω	

Authorized Reseller:	
·	
i i	
<u>.</u>	
:	
i	
:	
i i	
:	
:	
i	
1,	

The 289P is a lightweight, ergonomic radio that is manufactured in conformity with the European Union Radio Equipment Directive (RED 2014/53/EU) addressing human health-safety, EMC, and effective use of the radio spectrum. The 289P is the ideal assistant for staff members working in harsh environments and lengthy shifts thanks to its rugged case and 1750mah powerful battery.

### **RUGGED AND EASY TO USE**

289P is lightweight and portable making it easy to use and carry. It boasts a strong, top-notch, and impact-resistant casing.

## **SCANNING**

Calls on other channels can also be listened using the scanning feature of 289P.

## **LONG-LIFE BATTERY**

The 289P guarantees uninterrupted and effective operation of the staff with a single battery during lengthy shifts thanks to its powerful 1750mah Li-Ion Battery.

# CTCSS/DCS/DTMF

Supports CTCSS and DCS tone coded squelch systems and DTMF signals.

### VOX

Voice activated microphone enables hands free operation. 289P also supports external earpiece and microphone accessories.